



**10MM DIP346  
IMPACT RESISTANT  
CONFIGURATION**

FRONT ▶



## ● APPLICATION:

Purposed for outdoor fixed installations such as billboards or monument work, the ODX-P10D Outdoor offers high resolution video while retaining enough dependability and fortitude to withstand harsh conditions. With the backbone to handle inclement weather and a stunning image output that rivals its indoor-rated counterparts the ODX-P10D Outdoor is a flexible LED solution for nearly any outdoor application.

## ● TECHNICAL SPECIFICATIONS

- Pixel Pitch: 10mm
- Drive Method: 1/4
- LED Type: DIP346
- Brightness:  $\geq 6,500\text{cd/m}^2$
- Pixel Density: 10,000 pix/m<sup>2</sup>
- Viewing Angle: 120°H and 60°v
- Module Size: 160w x 160h mm (6.29 x 6.29 in)
- Cabinet Size: 960w x 960h mm (37.79 x 37.79 in)
- Cabinet Weight: 50kg (110.23 lbs)
- Cabinet Material: Sheet Metal
- Average/Max Power Consumption: 220W/650W
- Refresh Rate:  $\geq 1920\text{HZ}$
- Voltage : 110-240V
- IP Rating: IP65
- Operating Temperature : -20 - 50°C
- Life Span (hrs):  $\geq 50,000$
- Compliance Standard: CE, RoHS, CCC
- Typical Control System is NovaSTAR

◀ REAR



## ● FOR MORE INFORMATION:

**HIVELED.COM**  
**(800) 606-6165**