



SMD3535
BLACK BODY / WHITE FACE
HIGH CONTRAST



APPLICATION:

Designed for outdoor daylight rental applications, where quick installation and light-weight performance are essential. HIVE DCX Series delivers high resolution, high contrast images in a rigid yet light-weight diecast aluminum form factor. All cabinets in DCX series are 500mm x 500mm. Assembly is achieved through a precision tensionable bayonet system and allows panels to be removed from the center of an existing screen for easy maintenance.

TECHNICAL SPECIFICATIONS

- Pixel Pitch: 6.25mm
- Drive Method: 1/8
- LED Type: SMD3535
- Brightness: $\geq 5,000\text{cd/m}^2$
- Pixel Density: 25,600 pix/m²
- Viewing Angle: 140°H and 140°v
- Module Size: 250w x 250h mm (9.84 x 9.84 in)
- Cabinet Size: 500w 500h (19.68 x 19.68 x 3.46 in)
- Cabinet Weight: 6kg/24kg m² (13.2 lbs. 52.8 m²)
- Cabinet Material: Diecast Aluminium
- Average/Max Power Consumption: 200W/600W m²
- Refresh Rate: $\geq 1920\text{HZ}$
- Voltage : 100-240V
- IP Rating: IP31
- Operating Temperature : -20 - 50°C (10 - 90% RH)
- Life Span (hrs): $\geq 50,000$
- Compliance Standard: CE, RoHS, CCC
- Typical Control System is NovaSTAR



FOR MORE INFORMATION:

HIVELED.COM
800-628-9084