



● APPLICATION:

Designed for the ultimate flexibility between rental and fixed install applications, HIVE Simplex Series delivers high resolution, high contrast images in a rigid yet light-weight form factor. Two cabinet sizes are available that work together to form a number of easy to assemble, flexible screen variations.



◀ FRONT



REAR ▶

● TECHNICAL SPECIFICATIONS

- Pixel Pitch: 6.25mm
- Drive Method: 1/8
- LED Type: SMD3528
- Brightness: $\geq 1,200\text{cd/m}^2$
- Pixel Density: $25,600\text{pix/m}^2$
- Viewing Angle: 140°H and 120°V
- Module Size: $250\text{w} \times 250\text{h}$ mm (9.84 x 9.84 in)
- Cabinet Size: $500\text{w} \times 1000\text{h}$ mm (19.68 x 39.36 x 2.68 in)
- Cabinet Weight: $9\text{kg}/18\text{kg m}^2$ (19.85 lbs. 39.7 m^2)
- Cabinet Material: Aluminum Extruded Sheet Metal
- Average/Max Power Consumption: $300\text{W}/600\text{W m}^2$
- Refresh Rate: $\geq 1200\text{HZ}$
- Voltage : 100-240V
- IP Rating: IP31
- Operating Temperature : $-20 - 50^\circ\text{C}$ (10 - 90% RH)
- Life Span (hrs): $\geq 50,000$
- Compliance Standard: CE, RoHS, CCC
- Typical Control System is NovaSTAR

● FOR MORE INFORMATION:

HIVELED.COM
800-628-9084