




FRONT



REAR

APPLICATION:

Designed for the ultimate flexibility between rental and fixed install applications, HIVE Simplex Series delivers high resolution, high contrast images in a rigid yet light-weight form factor. Two cabinet sizes are available that work together to form a number of easy to assemble, flexible screen variations.

TECHNICAL SPECIFICATIONS

- Pixel Pitch: 6.25mm
- Drive Method: 1/8
- LED Type: SMD3528
- Brightness: $\geq 1,200\text{cd/m}^2$
- Pixel Density: 25,600pix/m²
- Viewing Angle: 140°H and 120°v
- Module Size: 250w x 250h mm (9.84 x 9.84 in)
- Cabinet Size: 500w 500h (19.68 x 19.68 x 2.68 in)
- Cabinet Weight: 5kg/20kg m² (11 lbs. 44 m²)
- Cabinet Material: Aluminum Extruded Sheet Metal
- Average/Max Power Consumption: 300W/600W m²
- Refresh Rate: $\geq 1200\text{HZ}$
- Voltage : 100-240V
- IP Rating: IP31
- Operating Temperature : -20 - 50°C (10 - 90% RH)
- Life Span (hrs): $\geq 50,000$
- Compliance Standard: CE, RoHS, CCC
- Typical Control System is NovaSTAR

FOR MORE INFORMATION:

HIVELED.COM
800-628-9084